

DATA SHEET



CLOTH TAPE (-40°C-125°C)

This tape mainly use for automobile wire harness. Easy to tear, waterproof, anti-aging. It can be flame-retardant, fireproof, used in the vehicle winding location, can reduce vibration, noise.

Item Code	Base Material			Size		Character						
	Material	Color	Adhesive	Length (m)	Width (mm)	Thickness (mm)	Tensile Strength (N/cm)	Elongation At Break (%)	Peel Adhesion to Steel (N/cm)	Operating Temperature Resistance (C°)	Peel Adhesion (N/cm)	Abrasion Resistance (time)
12015	Polyester Cloth	Black	Hot Melt Adhesive	25	19	0,16	≥65	10	2,5	-40—125	2.May	1000

1 The data above is typical and subject to change with notice

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. A strict use-by date of 3 months under temperature between +5°C and +25°C from the date of manufacture is recommended.

Shelf life from date of manufacture is valid when stored in a humidity controlled storage (10°C/50F to 27°C/80F and 40% to 75% relative humidity).

The users should take test and do trial-application on the above products before coming to application so as to witness and ensure suitability for their special purpose and technique.

Dimension tolerance of tape:

Thickness tolerance: ±5%

Width tolerance: ±0.5mm for widths up to and including 30mm; ±1.0mm for greater widths
length: ±30cm for lengths up to and including 25m, ±50cm for great lengths within 1 00m

For this product, please contact:

ERANOVA ENDÜSTRİ
ve ELEKTRİK MALZEMELERİ LTD. ŞTİ.

Perpa Trade Center, B Block 11th Floor,
No: 1643, Okmeydanı, Şişli / İstanbul - Turkey
Tel. +90 (212) 265 02 93 - Fax +90 (212) 381 79 69
satis@eranova.com.tr

ERANOVA
Endüstri ve Elektrik Malzemeleri Ltd. Şti.
Dynamic Solutions Worldwide

www.eranova.com.tr

All information, recommendations and test data herein are offered only as a guide. We believe them to be accurate but do not guarantee results, freedom from patent infringement, suitability of this product for any resultant application.