



## Terminal Block - DB500 500 AMPER

### TECHNICAL DATA

Body Material	Abs, Copper
Rated Current (A)	500A
Rated Voltage	690V
Dimensions	59 x 50 x 95mm
Input Section	Bara 3x15 - 8x24
Output Section	35 mm <sup>2</sup> * 2 Pcs/16 mm <sup>2</sup> * 5 Pcs/10 mm <sup>2</sup> * 4 Pcs
Copper Weight	294 gr.

### FEATURES

- Glade of flame retardant: UL94V-0
- Rail or screw mounting
- Transparent cover and screen
- Minimum space for maximum power
- Safe connections



Quick Code	Product Code	Rated Current (A)	Input		Output		L	H	W
			Section	Piece	Section	Piece			
41034	DB80	80 A	16 mm <sup>2</sup>	1	6 mm <sup>2</sup>	4	30	47	65
					16 mm <sup>2</sup>	2			
41035	DB125	125 A	35 mm <sup>2</sup>	1	16 mm <sup>2</sup>	6	30	47	74
			Köprü 16 mm <sup>2</sup>	1					
41036	DB160	160 A	70 mm <sup>2</sup>	1	16 mm <sup>2</sup>	6	30	47	74
			Köprü 16 mm <sup>2</sup>	1					
41037	DB250	250 A	120 mm <sup>2</sup>	1	35 mm <sup>2</sup>	2	49	50	95
					16 mm <sup>2</sup>	5			
					10 mm <sup>2</sup>	4			
41038	DB400	400 A	185 mm <sup>2</sup>	1	35 mm <sup>2</sup>	2	49	50	95
					16 mm <sup>2</sup>	5			
					10 mm <sup>2</sup>	4			
41039	DB500	500 A	Bara 3x15 - 8x24	1	35 mm <sup>2</sup>	2	59	50	95
					16 mm <sup>2</sup>	5			
					10 mm <sup>2</sup>	4			

For this product, please contact:

ERANOVA ENDÜSTRİ  
ve ELEKTRİK MALZEMELERİ LTD. ŞTİ.

Perpa Trade Center, B Block 11th Floor,  
No: 1828, Okmeydanı, Şişli / İstanbul - Turkey  
Tel. +90 (212) 265 02 93 - Fax +90 (212) 381 79 69  
satis@eranova.com.tr

**ERANOVA**  
Endüstri ve Elektrik Malzemeleri Ltd. Şti.  
Dynamic Solutions Worldwide

[www.eranova.com.tr](http://www.eranova.com.tr)

All information, recommendations and test data herein are offered only as a guide. We believe them to be accurate but do not guarantee results, freedom from patent infringement, suitability of this product for any resultant application.